

500029

Solvent 029 Extra Retardant

Retardant Solvent for high temperatures

**FEATURES**

|                  |                       |                               |  |
|------------------|-----------------------|-------------------------------|--|
| Properties:      | Very slow evaporation |                               |  |
| Recommended Use: | Retardant for         | intense heat or high humidity |  |
| How to use:      |                       |                               |  |
|                  |                       |                               |  |

**TYPICAL PROPERTIES (25 °C)**

|                  |               |  |  |
|------------------|---------------|--|--|
| Density (kg/L)   | 0.890 - 0.910 |  |  |
| VOC Content (%w) | 99.94         |  |  |
|                  |               |  |  |
|                  |               |  |  |

**OBSERVATIONS**

With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS.

Different solvents have different applications. Use every solvent for the purpose recommended for the manufacturer.

Expiry date: 1 year

|  |  |  |  |
|--|--|--|--|
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |
|  |  |  |  |

**Note:** the aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. // **Version 1. 02/03/2017**