

190021

Hardener PU 021 High Solids

Hardener for high solids polyurethane

**FEATURES**

Properties:	Good adhesion	Good re-coating white/clear sealer	Increases surface hardness
Recommended Use:	For Polyuretahne	Medium-slow drying	Improves elasticity
How to use:			

**TYPICAL PROPERTIES (25 °C)**

Density (kg/L):	0.970-1.050		
MNV (%):	33-35.50		
VOC (%):	67.50		

**OBSERVATIONS**

Keep the can properly closed after using the product, unless it will get spoiled due to its reactivity with environmental humidity. Once the can is opened, it ought to be used as soon as possible.

We recommend to keep the product at a temperature between 5 and 35°C, avoiding direct sun exposures of the containers.

Expiry date: 1 year (Under mentioned conditions)

Check TDS of the first component.

With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS


**Note:** the aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. // **Version 1. 02/03/2017**