

190046	Hardener PU 042 Colours
--------	-------------------------

Hardener for polyurethane topcoats

FEATURES

Properties:	Non yellowing	Quick drying	High solids
Recommended Use:	For Polyurethane	White polyurethane topcoats	Improves surface hardness
How to use:			

TYPICAL PROPERTIES (25 °C)

Density (kg/L):	0.970-0.990		
MNV (%):	29-32		
VOC (%):	69.59		

OBSERVATIONS

Keep the can properly closed after using the product, unless it will get spoiled due to its reactivity with environmental humidity. Once the can is opened, it ought to be used as soon as possible.

We recommend to keep the product at a temperature between 5 and 35°C, avoiding direct sun exposures of the containers.

Expiry date: 1 year (Under mentioned conditions)

Check TDS of the first component.

With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS

Note: the aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. // **Version 1. 02/03/2017**